# **Test Report**

Report Number: 128502-19-ST



TECHNOLOGICAL INSTITUTE

Gregersensvej 1 DK-2630 Taastrup +45 72 20 20 00 info@teknologisk.dk www.teknologisk.dk

Page 1 of 3 Init.: JNAS/JHA Order no.: 128502

Encl.: 2

Assignor: HAY APS, Havnen 1, DK-8700 Horsens

Item: Arc Trolley High - the test also covers Arc Trolley Low

Sampling: The assignor confirms having selected the product. The product was forwarded by the

assignor and received at Danish Technological Institute on 19 April 2022.

**Period:** The test took place from 25 April 2022 to 5 May 2022.

Method: EN 15372:2016, Furniture - Strength, durability and safety - Requirements for non-domestic

tables

Test severity L3: Severe use: E.g. in night-clubs, police stations, transport terminals, hospital public areas, casinos, homes for the elderly, sports changing rooms, prisons, barracks.

Additional information is given in enclosure B.

**Test results:** Passed.

The results are shown in enclosure A.

Terms: This test was conducted accredited in accordance with international requirements (ISO/IEC

17025:2017) and in accordance with the General Terms and Conditions of Danish

Technological Institute. The test results solely apply to the tested item. This test report may be quoted in extract only if Danish Technological Institute has granted its written consent.

**Place:** Danish Technological Institute, Taastrup, Building and Construction

Signature: This document is only valid with a digital signature from Danish Technological Institute. The

date of issue appears from the digital signature.

Jacob Næsby Consultant









# Results

Test No.	Test	Test Method	Loading		Result			
5.1	General requirements							
5.2.1	Shear and squeeze points when setting up and folding							
5.2.2	Shear and squeeze points under influence of powered mechanisms							
5.2.3	Shear and squeeze points during use	r and squeeze points during use						
5.4.1-1	Horizontal static load test	EN 1730, 6.2	Test force, N Specified mass, kg Cycles	230 50 10	Passed			
Comment	Horizontal loading reduced from 600 N to 230 N to avoid tilting.							
5.4.1-2	Vertical static load on main surface	EN 1730, 6.3.1	Test force, N Cycles	1250 10	Passed			
5.4.1-3	Additional vertical static load test where the main surface has a length >1600 mm	EN 1730, 6.3.2	Test force, N Cycles	1000 10	N/A			
5.4.1-4	Vertical static load on ancillary surface	EN 1730, 6.3.3	Test force, N Cycles	300 10	N/A			
5.4.1-5	Horizontal durability test	EN 1730, 6.4.1 and 6.4.2	Test force, N 30 Specified mass, kg 50 Cycles 200		Passed			
5.4.1-6	Vertical durability test for cantilever and tables with central column only	EN 1730, 6.5	Test force, N Cycles	300 20000	N/A			
5.4.1-7	Vertical impact test for glass tabletops	EN 1730, 6.6.1 and 6.6.2	Drop height, mm 240 Cycles 10		N/A			
5.4.1-8	Vertical impact test for all other tabletops	EN 1730, 6.6.1 and 6.6.3	Drop height, mm Cycles	180 10	Passed			
5.4.1-9	Drop test – This test is applicable for tables weighing more than 20 kg only	EN 1730, 6.9	Drop height, mm Cycles	50 6	Passed			
5.4.1-10	Stability under vertical load test	EN 1730, 7.2	Main surface Ancillary surface	200 100	Passed			
5.4.1-11	Stability for tables with extension elements	EN 1730, 7.3	Test force, N	200	N/A			
6	Information for use							
A.3.2	Durability of table with castors	EN 1730, 6.8	Specified load, N Cycles	20 2000	Passed			



# Information provided by the Danish Technological Institute

### Photograph of the received sample



# Information required by EN 15372:2013

#### European Standards used:

EN 15372:2016 - Furniture - Strength, durability and safety - Requirements for non-domestic tables

EN 1730:2012 - Furniture - Tables - Test methods for the determination of stability, Strength and durability

#### Details of tested table:

Model:	Arc Trolley High			Type:	Trolley			
Width:	465 mm	Length:	675 mm	Height:	877 mm	Weight:	22.5 kg	
Materials:	Metal							

#### Details of defects observed before testing:

None.

### Details of any deviations from this standard:

None.

### Any variation from the specified temperature range:

None.

#### Test result:

See enclosure A.

#### Name and address of the test facility:

Danish Technological Institute, Gregersensvej, Taastrup 2630, Denmark

#### Date of test:

2022-04-25 to 2022-05-05